

GLIDESCOPE®

Video Laryngoscope

Designed for 1st Pass Success

RANGER

Single Use

Optimized for demanding ED, ICU, OR, and pre-hospital applications, the GlideScope® Ranger Single Use Video Laryngoscope provides a clear, real time view of the airway and of endotracheal tube placement.

In fast-paced intubation settings, disinfecting a reusable airway device takes time you may not have. With the GlideScope® Ranger Single Use, there's no waiting for disinfection. This compact video laryngoscope is operational in seconds.

Designed to military specifications, the combination of a single-use, sterile Ranger GVL® Stat and GlideScope® Ranger Video Baton is ideal for crash cart, military and EMS use.

- Reusable video baton with high-resolution camera and anti-fogging mechanism to resist lens contamination
- Non-glare color monitor easily visible in bright light
- Single-use, sterile GVL® Stats in two sizes
- Patented 60° blade angulation
- Easy to learn, use, and teach



Designed for a variety of field conditions

- Rugged, durable construction
- Compact size for easy carrying and storage (7 1/4" x 6 3/8")
- Lightweight for maximum portability (< 1 3/4 lbs)
- Altitude up to 20,000 feet
- Temperatures of -4° to +122° F
- Humidity up to 100%

Ranger models are based on the GlideScope® GVL®, which achieves a C-L Grade I or II view 99% of the time.¹

Reference: 1. Cooper, RM. Cardiothoracic Anesthesia, Respiration and Airway; Early clinical experience with a new video laryngoscope (GlideScope®) in 728 patients. *Canadian Journal of Anesthesia* 2005; 52: 2: 191-198. GlideScope® GVL®, Verathon® and Verathon Medical® are either registered trademarks or trademarks of Verathon Inc. in the United States and/or other countries. All rights reserved. © Copyright 2007 Verathon Inc.

 **VERATHON**
MEDICAL

GLIDESCOPE®

Video Laryngoscopes

Designed for 1st Pass Success

RANGER

Single Use

About the System:

- 3 ½ inch color video **monitor** in soft-pack case
- **Video Baton**, carrying case, and protective cradle
- **GVL® Stat**—single-use, sterile blade

Large GVL® Stat

Patient Weight: approx. 88 lbs to morbidly obese
Blade Length (tip to handle): 95.0 mm
Blade Thickness (max): 16.5 mm
Blade Width (max): 27.5 mm

Small GVL® Stat

Patient Weight: less than 88 lbs
Blade Length (tip to handle): 80.0 mm
Blade Thickness (max): 16.5 mm
Blade Width (max): 21.0 mm

- Integrated, rechargeable lithium polymer battery
- Medical grade recharger operates at 50-60 Hz and 100-250 V
- User's Manual and Quick Reference Cards
- 1-year warranty



Applications

- Pre-hospital (field) airway treatment
- Level 1, 2 and 3 Military medicine casualty centers
- Intubation with cervical spine immobilization
- Trauma airways – excellent when dealing with blood & secretions in the airway
- Challenging airways (DL Grades I-IV)
- First use intubations, replacing DL

Call 800.331.2313 today for more information,
or visit www.verathon.com.



The GlideScope® video laryngoscopy systems are CE marked in accordance with the Medical Device Directive, and the Verathon Inc. quality system is Quality System Certified to ISO 13485:2003 standards. US Patent No. 6,655,377; 6,543,447; International patents pending.



Corporate Headquarters
20001 North Creek Parkway / Bothell, WA 98011-8218 USA
425.867.1348 / 800.331.2313 / 425.883.2896 Fax
www.verathon.com